

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.



THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of )  
)  
Kevin M. McHugh )  
)  
Serial No. 09/592.003 ) Examiner: Leyson  
)  
Filed 06/12/00 ) Group Art Unit: 1722  
)  
Atty. Dkt.: EGG-PI-612A1a )  
)  
For: Rapid Solidification )  
Processing System for )  
Producing Molds, Dies and )  
Related Tooling )  
\_\_\_\_\_ )

6/KW  
3/5/02

RECEIVED  
FEB 25 2002  
TC 1700

Assistant Commissioner for Patents  
Washington, D.C. 20231  
Attention: Official Draftsman

**SUBSTITUTE DRAWINGS REQUEST**

Please enter the enclosed substitute drawing sheet 5 in the above-referenced application in place of the originally filed drawing sheet. The substitute drawing sheet 5 is being submitted to correctly label Fig.s 4A, 4B and 4C that were inadvertently mislabeled in the drawing sheet as originally filed. A red-inked copy of drawing sheet 5 showing correctly labeled figures is

**CERTIFICATE OF MAILING/TRANSMISSION (37 CFR 1.8a)**

I hereby certify that this correspondence is, on the date shown below, being:

**MAILING**

☒ deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to the Assistant Commissioner for Patents, Washington D.C. 20231

Date: \_\_\_\_\_

**FACSIMILE**

☐ transmitted by facsimile to the Patent and Trademark Office.

MANDY LANDON

(Type or print name of person certifying)

Signature

submitted along with the formal drawing sheet 5. No new matter is contained in the new drawing sheet.

Acknowledgment of receipt of the formal drawing sheet and its acceptance into the file is requested.

RESPECTFULLY SUBMITTED.

By Alan D. Kirsch

Alan D. Kirsch

Patent Attorney

Reg. No. 33,720

P.O. Box 1625

Idaho Falls, Idaho 83415-3899

Date 1/30/02

(208)-526-1371

**Enclosures:** Substitute Formal Drawing Sheet 5; Red-inked copy of Drawing Sheet 5.

## Nozzle Information

• Nozzle Information:	14.0°
• Exit Angle	14.0°
• Distance from Liquid Orifice to Nozzle Exit (inches)	1.018
• Number of Orifices	6.0
• Orifice Area (square inches)	0.000314
• Total Area of Liquid Orifices (square inches)	0.0019
• Cross Sectional Area of Nozzle Throat (square inches)	0.06
• Cross Sectional Area of Gas Stream at Nozzle Exit (square inches)	0.266

Fig. 4A

Run Time (sec)	TC #1 (°C)	TC #2 (°C)	TC #3 (°C)	TC #4 (°C)	TC #5 (°C)	TC #6 (°C)	Argon TC #7 (°C)	Gas Flow (slpm)
45.5	309.7	165.3	107.7	100.6	86.0	79.5	74.8	253.7
105.5	318.8	190.5	122.6	113.5	92.9	83.9	79.1	283.6
165.5	318.0	199.0	129.8	120.1	97.3	87.0	81.6	305.8
215.5	324.6	201.3	134.5	124.8	101.0	90.0	83.9	329.5
285.5	311.7	200.0	136.0	127.0	102.5	91.1	85.2	355.9
345.5	295.9	196.6	135.3	127.0	102.5	90.6	84.6	381.2
405.5	279.9	194.4	135.1	127.2	102.9	91.2	85.1	412.2
465.5	266.9	190.6	133.4	126.2	101.9	90.6	84.1	439.3
525.5	251.8	186.0	131.9	125.4	101.4	90.1	84.2	474.7
585.5	233.4	180.1	130.3	123.8	100.4	89.5	83.7	504.5

Distance from Nozzle Exit (inches)

0.125 1.25 2.25 3.25 4.375 5.312 6.187

Fig. 4B

Gas Temperature Nozzle Inlet (°C)	Nozzle Temperature Liquid Orifice (°C)	Chamber Temperature (°C)	Nozzle Inlet Pressure (psia)
552.7	347.9	38.0	15.096
555.8	356.7	39.0	16.168
557.2	362.7	39.7	17.074
548.5	365.0	40.0	18.020
527.3	364.1	41.1	19.003
501.7	359.3	41.9	19.926
476.0	350.9	42.0	20.982
453.9	340.9	43.4	21.928
429.2	329.3	44.0	23.054
409.0	317.4	44.1	23.968

Fig. 4C

## Nozzle Information

• Nozzle Information:	14.0°
• Exit Angle	14.0°
• Distance from Liquid Orifice to Nozzle Exit (inches)	1.018
• Number of Orifices	6.0
• Orifice Area (square inches)	0.000314
• Total Area of Liquid Orifices (square inches)	0.0019
• Cross Sectional Area of Nozzle Throat (square inches)	0.06
• Cross Sectional Area of Gas Stream at Nozzle Exit (square inches)	0.266

Fig. 4A

Run Time (sec)	TC #1 (°C)	TC #2 (°C)	TC #3 (°C)	TC #4 (°C)	TC #5 (°C)	TC #6 (°C)	Argon TC #7 (°C)	Gas Flow (slpm)
45.5	309.7	165.3	107.7	100.6	86.0	79.5	74.8	253.7
105.5	318.8	190.5	122.6	113.5	92.9	83.9	79.1	283.6
165.5	318.0	199.0	129.8	120.1	97.3	87.0	81.6	305.8
215.5	324.6	201.3	134.5	124.8	101.0	90.0	83.9	329.5
285.5	311.7	200.0	136.0	127.0	102.5	91.1	85.2	355.9
345.5	295.9	196.6	135.3	127.0	102.5	90.6	84.6	381.2
405.5	279.9	194.4	135.1	127.2	102.9	91.2	85.1	412.2
465.5	266.9	190.6	133.4	126.2	101.9	90.6	84.1	439.3
525.5	251.8	186.0	131.9	125.4	101.4	90.1	84.2	474.7
585.5	233.4	180.1	130.3	123.8	100.4	89.5	83.7	504.5

Distance from Nozzle Exit (inches)

0.125 1.25 2.25 3.25 4.375 5.312 6.187

Fig. 4B

Gas Temperature Nozzle Inlet (°C)	Nozzle Temperature Liquid Orifice (°C)	Chamber Temperature (°C)	Nozzle Inlet Pressure (psia)
552.7	347.9	38.0	15.096
555.8	356.7	39.0	16.168
557.2	362.7	39.7	17.074
548.5	365.0	40.0	18.020
527.3	364.1	41.1	19.003
501.7	359.3	41.9	19.926
476.0	350.9	42.0	20.982
453.9	340.9	43.4	21.928
429.2	329.3	44.0	23.054
409.0	317.4	44.1	23.968

Fig. 4B

29.40